



Model #: 40-6226 UPC: #049448062263



The perfect addition to your dot laser - these pre-threaded accessories allow you to reshape the beam to a diameter of either 1/16", 3/32" or 1/8" for a more precise dot. They screw directly into the laser housing, for a quick and easy solution to your dot laser needs.

PRODUCT DETAILS

- Exclusive Solid Brass Aperture Pack works with all three dot laser modules
- Pre-threaded accessories screw directly into the pre-threaded Alignment Laser housing allowing the user to lower the laser beam intensity while reshaping the beam to 1/16", 3/32" or 1/8" Diameters.

SPECIFICATIONS

Beam Divergance	70 degree standard
Dimensions	4" x 0.75" x 1.375" (101x19x35)
Interior Range	Up to 100ft. (30m) 40-6230 and 150ft. (45m) 40-6232 depending upon light conditions
IP Protection Class	65
Laser Classification	Class II
Laser Wavelength	532nm (Green), 635nm+/-10nm (Red)
Maximum Power Output	Less than/Equal to 1mW
Power Supply	110AC (included)
Warranty	1 Year Warranty
Weight	7.5 oz. (.21kg)

APPLICATION

These accessories were designed to use with Johnson's model 40-6220, 40-6222 and 40-6224 dot lasers. They give you greater versatility with the diameter and intensity of the laser beam - making them ideal for positioning parts on equipment, drill press alignment, site layout, crosscut and break measurements, grading, slope projects and more!



For additional information on Johnson products, please contact Customer Service at 888.953.8357 or service@johnsonlevel.com www.johnsonlevel.com | © Johnson Level & Tool Mfg. Co. Inc.