

High Accuracy Dual Slope Rotary Laser Kit

Model #: 40-6535
UPC: #049448065356



This rotary laser kit is the simplest way to get your outdoor job up and running. With simple set-up and visual and audible alarms to alert you when the rotary is beyond its leveling range, you can quickly get the information you need with guaranteed accuracy. And the included remote control and detector allow for one-person operation. The laser's electronically controlled dual-slope mode takes math out of the equation when checking grade or setting drainage, while its electronic self-leveling in the horizontal plane is ideal for excavation and concrete work. With the included NiMH rechargeable battery pack and charger, remote control with 9V battery, detector with 9V battery and clamp, and hard-shell carrying case, this kit comes equipped with everything you need for your next outdoor jobsite!

PRODUCT DETAILS

40-6535 Kit Includes > Laser, NiMH rechargeable battery pack and charger, remote control with 9V battery, detector with 9V battery and clamp, and hard-shell carrying case.

- Designed for outdoor use and simple set up
- Electronically-controlled dual slope feature
- Electronic self-leveling in the horizontal plane
- Visual and audible alarms when beyond leveling range
- Slope operation function allows user to perform slope 8 degrees in both x and y axis
- Remote control and detector for one person operation
- Height of Instrument/Tilt alarm function ensures product accuracy

SPECIFICATIONS

Accuracy	±1/16"/100
Auto-Leveling Range	±5°
Battery Life	28 hours NiMH; 33 hours alkaline batteries
Center Screw Thread	5/8"-11
Dimensions	7.4" x 5.9" x 8.15"
Exterior Range	Up to 2,000' diameter
Interior Range	Up to 200' diameter
IP Protection Class	66
Laser Classification	Class IIIa
Laser Wavelength	635nm±10nm (Red)
Leveling Method	Automatic (Electronic)
Maximum Power Output	±5mW
Power Supply	NiMH rechargeable battery pack and charger (included), 4 "C" alkaline batteries (not included)
Remote Range	Up to 200' diameter
Rotation Speeds	800 RPM
Slope	±8°
Warranty	3 Years
Weight	5.51 LBS
Working Temperature	14°F-113°F

APPLICATION

The rotary's self-leveling feature in the horizontal mode makes it ideal for excavation, concrete and other outdoor applications, while the electronically controlled dual-slope mode makes this laser ideal for drainage, flatwork or complex landscaping jobs.



For additional information on Johnson products, please contact
Customer Service at 888.953.8357 or service@johnsonlevel.com
www.johnsonlevel.com | © Johnson Level & Tool Mfg. Co. Inc.