

High Accuracy Dual Slope Rotary Laser System

Model #: 40-6541
UPC: 049448065417



Designed with the excavator, flatwork contractor, or landscaper in mind, this horizontal-only rotary features a wide dual-slope range of 8°. One of our easiest to operate and quickest leveling rotaries, you'll be up and running in no time with the 40-6541 laser.

PRODUCT DETAILS

40-6541 Includes > Laser, NiMH rechargeable battery pack and charger, remote control with 9V battery, detector with clamp and 9V battery, tripod, 13' grade rod, magnetic target, tinted glasses, and hard-shell carrying case

- Electronic self-leveling in the horizontal plane
- 8° dual-slope simplifies grading and concrete flatwork
- Visual and audible alarms when beyond leveling range
- Tilt indicator alerts operator if the laser is bumped or moved
- Includes everything to grade or level your jobsite
- Includes full size 13' grade rod

SPECIFICATIONS

Accuracy	±1/16"/100'
Battery Life	28 hours NiMH; 33 hours alkaline batteries
Exterior Range	Up to 2,000' diameter with detector
Interior Range	Up to 200' diameter
IP Protection Class	66
Laser Classification	Class IIIa
Laser Wavelength	635nm±10nm
Leveling Method	Automatic (Electronic)
Maximum Power Output	≤5mW
Power Supply	NiMH rechargeable battery pack and charger (included), 4 "C" alkaline batteries (not included)
Remote Range	Up to 200' diameter with remote
Rotation Speeds	800 RPM
Self-Leveling Range	±5°
Slope	±8°
Warranty	3 Years
Working Temperature	14°F-113°F

APPLICATION

High-accuracy horizontal work including excavation, flatwork, landscaping, masonry, and form, post, and footing heights. Indoors use for drop ceilings, beams, and more!



For additional information on Johnson products, please contact
Customer Service at 888.953.8357 or service@johnsonlevel.com
www.johnsonlevel.com | © Johnson Level & Tool Mfg. Co. Inc.