

JLX® Horizontal/Vertical Tracking Rotary System with GreenBrite® Technology

Model #: 40-6590
UPC: 049448065905



Level Up® to a tracking rotary. Simplify long-distance layout work and turn a two person job into a single person job. Set reference lines with ease, work indoors or outdoors. With the 40-6590 tracking rotary, you'll get everything you need to level your jobsite, both indoors and out, including a tripod, grade rod, vertical floor mount, detector, and remote control.

PRODUCT DETAILS

40-6590 Includes > NiMH battery and charger, 4 "C" alkaline battery compartment (batteries not included), detector with clamp and 4 "AA" alkaline batteries, remote control with 2 "AA" alkaline batteries, tinted glasses, magnetic target, vertical bracket, 13' grade rod, tripod, instruction manual, and hard-shell carrying case

- GreenBrite® Technology - 400% more visible
- Tracks to the detector position for simple reference line layout
- Horizontal / Vertical Operation - track in either plane
- Vertical mode is ideal for layout of walls or forms
- Slope track / Slope match to 5° in both the X and Y axes
- Bright, Class 3 green beam laser is the most visible laser for indoor work
- Tilt indicator alerts operator if the laser is bumped or moved
- Includes everything to grade or level your jobsite, including a full 13' grade rod

SPECIFICATIONS

Accuracy	±3/32"/100'
Battery Life	18 hours with NiMH; 16 hours with alkaline
Center Screw Thread	5/8"-11
Dimensions	7.95" x 8.62" x 6.29"
Exterior Range	Up to 1,500' diameter with detector
IP Protection Class	54
Laser Classification	Class III
Laser Wavelength	520nm±10nm
Leveling Method	Automatic (Electronic)
Maximum Power Output	≤5mW
Power Supply	NiMH or 4 "C" alkaline batteries
Remote Range	Up to 200' diameter with remote
Rotation Speeds	300 and 800 RPM
Scanning Modes	0°, 30°, 60°
Self-Leveling Range	±5°
Warranty	3 Years
Working Temperature	32°F-104°F

APPLICATION

Layout work including framing, drywall track, and tilt-up. Also ideal for other interior applications such as drop ceilings, wainscoting, and more. Can be used outside for grading and excavation.



For additional information on Johnson products, please contact
Customer Service at 888.953.8357 or service@johnsonlevel.com
www.johnsonlevel.com | © Johnson Level & Tool Mfg. Co. Inc.