

Tiling Laser

Model #: 40-6624
UPC: 049448066247



Laser beams project over wet mastic or concrete. Perpendicular lasers form a 90° reference for flooring installation. Dual leveling vials for use on vertical surfaces. Ruled ends - inch, metric, and angle. 40-6624 INCLUDES > Laser, 2 "AA" alkaline batteries.

PRODUCT DETAILS

- Perpendicular lasers form a 90° reference for floor installation
- Dual leveling vials for use on vertical surfaces
- Ruled ends – inch, metric and angle
- Laser beams project over wet mastic or concrete

SPECIFICATIONS

Accuracy	±1/4"/20'
Battery Life	20 hours continuous use
Dimensions	6.1" x 0.61" x 1.9"
IP Protection Class	IP 50
Laser Classification	Class II
Laser Wavelength	635nm+10nm (Red)
Leveling Method	Manual (vials)
Maximum Power Output	<1mW
Power Supply	2 "AA" alkaline batteries (included)
Warranty	2 years
Weight	4.6 oz without the batteries
Working Range	Up to 23'
Working Temperature	32° F to 104° F



APPLICATION

The Johnson Level 40-6624 can be used for the following indoor applications; layout of tile, stone, brick, carpet and hardwood flooring.



For additional information on Johnson products, please contact
Customer Service at 888.953.8357 or service@johnsonlevel.com
www.johnsonlevel.com | © Johnson Level & Tool Mfg. Co. Inc.