

## Self-Leveling 3 Dot Laser

**Model #:** 40-6646  
**UPC:** 049448066469



3-Dot lasers are the most common dot laser, and for good reason. In most framing applications, these lasers can replace levels and plumb bobs, and are great for plumbing walls, checking floor level, transferring reference points from floor to ceiling, and leveling posts and beams, and setting drainage slopes.

### PRODUCT DETAILS

40-6646 Includes > Laser and 2 "AA" alkaline batteries

- Projects 2 plumb dots and 1 level dot
- Tall profile for clearance of wood or metal drywall track
- Visual out-of-level indicator
- 1/4"-20 tripod thread for use with most common tripods
- Dust resistant construction
- Locking compensator protects pendulum during transport

### SPECIFICATIONS

Accuracy	±1/8"/30'
Battery Life	20 hours continuous use
Dimensions	3.6" x 2.6" x 4.5"
IP Protection Class	IP 50
Laser Classification	Class II
Laser Wavelength	650nm±10nm (Red)
Leveling Method	Self-Leveling (Pendulum)
Maximum Power Output	≤1mW
Power Supply	2 "AA" alkaline batteries (included)
Self-Leveling Range	±5°
Warranty	2 years
Weight	9.9 oz (without batteries)
Working Range	Up to 100'
Working Temperature	32° F to 104° F



## APPLICATION

The Johnson Level 40-6646 can be used for the following indoor applications; flooring, cabinetry, drop ceiling installation, wainscoting, carpentry, tiling, electrical boxes and switches, drywall track/stud wall installation, setting drainage slope.



For additional information on Johnson products, please contact  
Customer Service at 888.953.8357 or [service@johnsonlevel.com](mailto:service@johnsonlevel.com)  
[www.johnsonlevel.com](http://www.johnsonlevel.com) | © Johnson Level & Tool Mfg. Co. Inc.