## **Self-Leveling Cross-Line Laser**

Model #: 40-6650 UPC: #049448066506



Johnson's 40-6650 Self-Leveling Cross-Line Laser comes with a magnetic bracket so it can attach to all ferrous metal surfaces for hands free use. This laser also can project one horizontal, vertical or cross-line beam simultaneously or individually.

## **PRODUCT DETAILS**

40-6650 Includes > Laser, multi-functional elevating magnetic bracket, mounting strap, 4 "AA" alkaline batteries, and softsided pouch

- Pulse mode for use with line detector (sold separately)
- Projects one horizontal, vertical or cross-line beam separately or simultaneously
- Locking compensator
- Visual out of level indicator
- Multi-function elevating magnetic bracket with rare earth magnets for use on walls, metallic surfaces or tripod
- While on bracket, the laser can be raised or lowered 2-1/2" and rotate 360°



## **SPECIFICATIONS**

Accuracy	±1/8"/35ft.
Battery Life	24 hours Li-ion; 16 hours alkaline *battery life as tested with Lithium AA/Alkaline AA batteries and all beams enabled
Center Screw Thread	5/8"-11, 1/4"-20
Dimensions	5.25" x 2" x 6"
Interior Range	Up to 200 ft; Dectector range up to 75ft. (With Johnson model 40-6780)
IP Protection Class	54
Laser Classification	Class II
Laser Wavelength	650nm±10nm (Red)
Leveling Method	Self-leveling (Pendulum)
Maximum Power Output	≤1mW
Power Supply	4 "AA" alkaline batteries (included); Li-ion rechargeable battery pack (not included)
Self-Leveling Range	±3 degrees
Warranty	3 Year Warranty
Weight	1.425 lbs (0.7kg)
Working Temperature	14°F to 113°F

## **APPLICATION**

The Johnson Level 40-6650 can be used for the following indoor applications; drop ceilings, drywall installation, sprinkler installation, HVAC, ceiling joint and rafter alignment, wallpaper and stenciling/painting, tiling (walls and floors), electrical outlets and switches, install conduit and wiring, track lighting, curtain walls/shower doors, windows, cabinet and countertop alignment, paneling/wainscoting.



For additional information on Johnson products, please contact Customer Service at 888.953.8357 or service@johnsonlevel.com www.johnsonlevel.com | © Johnson Level & Tool Mfg. Co. Inc.