



## Self-Leveling Cross-Line Laser with GreenBrite® Technology

Model #: 40-6657 UPC: 049448066575



Johnson's 40-6657 Self-Leveling Cross-Line Laser comes with a magnetic bracket so it can attach to all ferrous metal surfaces for hands free use. This laser also can project one horizontal, vertical or cross-line beam simultaneously or individually. Made with GreenBrite® Technology, this laser's green beam is 400% more visible than red beams. It even adds a pulse mode for the cross lines for use with a detector (sold seperately), for use where the lines aren't visible, such as in bright light or outdoor conditions.

## **PRODUCT DETAILS**

40-6657 Includes > Laser, multi-functional elevating bracket, magnetic target, mounting strap, 4 "AA" alkaline batteries, and hard-shell carrying case

- GreenBrite® Technology 400% more visible
- Pulse mode for use with line detector (sold separately)
- Locking compensator protects pendulum during transport
- Multi-Functional magnetic elevating bracket with rare earth magnets for use on walls, metallic surfaces or tripod.
- Projects horizontal, vertical or cross-line beam separately or simultaneously
- Visual out-of-level indicator
- While on the bracket, the laser can be rasied or lowered 2 1/2" and rotate 360°



For additional information on Johnson products, please contact Customer Service at 888.953.8357 or service@johnsonlevel.com www.johnsonlevel.com | © Johnson Level & Tool Mfg. Co. Inc.





## **SPECIFICATIONS**

Accuracy	±1/8"/35 ft.
Battery Life	11 Hours Li-ion. 6 Hours alkaline* *Battery life as tested with Lithium AA/Alkaline AA batteries, and all beams enabled.
Interior Range	Up to 200 ft.; Detector range up to 75 ft. (with Johnson model 40-6763 green beam laser detector, sold separately)
IP Protection Class	54
Laser Classification	Class II
Laser Wavelength	520nm±10nm (Green)
Leveling Method	Self-leveling (Pendulum)
Maximum Power Output	<1mW
Power Supply	4 "AA" alkaline batteries (included); Li-ion rechargeable battery pack (not included)
Self-Leveling Range	± 3 degrees
Warranty	3 Year Warranty
Working Temperature	14° F to 113° F

## **APPLICATION**

The Johnson Level 40-6657 can be used for the following indoor applications; drop ceilings, drywall installation, sprinkler installation, HVAC, ceiling joint and rafter alignment, wallpaper and stenciling/painting, tiling (walls and floors), electrical outlets and switches, install conduit and wiring, track lighting, curtain walls/shower doors, windows, cabinet and countertop alignment, soffits, chair rail/trim, closet shelves/drawers, paneling/wainscoting.



For additional information on Johnson products, please contact Customer Service at 888.953.8357 or service@johnsonlevel.com www.johnsonlevel.com | © Johnson Level & Tool Mfg. Co. Inc.