


EasyTwist Connector Layout

<b>Closed End Connectors</b> *Made from nylon 6/6 (Polyimide 66) *UL 94V-2 self extinguishing *Temperature rating to 105C and 300 Volts				Dimensional Data (In Inches)					Wire Combinations				
				E Length/Height	A I.D.	B Max. Skirt Entry	C Max. width	D Max. Skirt Depth	Max. Wire Combination	Min. Wire Combination			Temp Rating
<b>Nylon Closed End</b>	C22-N	22-18 AWG	Natural	0.709	0.102	0.244	0.307	0.236	(2)#20 w(1)#18	(2)#22 AWG	105 C	300 V	
	C22-N-B			0.787	0.118	0.311	0.374	0.276	(1)#18 w(1)#14	(2)#22 AWG			
	C16-N	22-14 AWG		1.004	0.173	0.413	0.492	0.378	(3)#14 AWG	(2)#22 W(2)#18			
	C16-N-B			1.091	0.209	0.488	0.563	0.472	(2)#16 W(1)#10	(2)#16 W(1)#12			
	C12-N	22-10 AWG											
	C12-N-B												
C8-N	16-10 AWG												
C8-N-B													
Nsi Industries LLC, 9730 Northcross Center Ct., Huntersville NC 28078 PH# 800-321-5847 FX# 800-841-5566 Email: <a href="mailto:sales@nsiindustries.com">sales@nsiindustries.com</a> -or- Additional Technical Data Available on the NSi website ... <a href="http://www.nsiindustries.com">www.nsiindustries.com</a>													