


NPDB-112A-350-1

	PRODUCT INFORMATION	FEATURES
	NPDB Series PDB, SCCR RMS SYM amps of 100kA rated with AL or CU conductors and proper fusing.	<ul style="list-style-type: none"> 100kA Short Circuit Current Rated (SCCR) Finger Safe IP20 per IEC60529 DIN Rail Mount - 35mm Multi-Pole Ganging

OVERVIEW	COLOR	MATERIAL	OVERCURRENT PROTECTION	ADDITIONAL FEATURES	CERTIFICATIONS
	Black Base, Clear Finger-Safe Panels and Cover	<ul style="list-style-type: none"> Base: Valox Nylon 6/6 Finger-Safe Panels and Cover: Lexan 500R Polycarbonate Connector: 6061-T6 AL, Electro-tin Plated 	Fuse Class and (Max. Amp): Class J (110A) Class T (110A) Class RK1 (60A) Class RK5 (30A) Class G (60A) Class CC (30A)	<ul style="list-style-type: none"> Replacement Cover P/N: CLNPDB Locking Mechanism to lock/release block on DIN Rail 35mm DIN Rail Mountable 	<ul style="list-style-type: none"> UL1953 and UL1059 Listed, cULus Finger Safe IP20 per IEC60529

TECHNICAL INFORMATION	CHARACTERISTIC	SPECIFICATION / VALUE
	Type	Single Primary (Line), Single Secondary (Load)
Wire range (Primary - Secondary)	PDB, 1 POLE: LINE 1 x 350-6, LOAD 12 x 4-14	
Conductor stranding class	Class B, C	
Torque data (in.lbf.)	Primary Max: 375 - Secondary Max: 35	
Wire strip length (in.)	Primary Max: 1.0 - Secondary Max: 0.5	
Maximum ampacity/pole	310A	
Dimensional size	SMALL - L: 5.80" x W: 1.95" x H: 3.75"	
Voltage rating	600V	
Operating temperature (°C)	90	
AL9CU	Dual-rated for use with copper or aluminum conductor	
Mounting	Slotted holes in base, 35mm DIN rail with locking feature	
Application	Splicing or Tapping of 1-2 Primary (Line/Main) Conductors to 1-12 Secondary (Load/Tap) Side Conductors	