




REV	DATE	REVISED	BY	ECN	C'K'D
A		RELEASED			
B	7/31/23	UPDATED ITEM SPECIFICATION	DC	23-00015	SSM
C	6/3/24	UPDATED TORQUE VALUE AND ADD NOTES 23/24	XGP	24-00073	SSM

FUSE TABLE	
Overcurrent Protection, Fuse Required Class	Maximum Amp Rating
Class J	110A
Class T	110A
Class RK1	60A
Class RK5	30A
Class G	60A
Class CC	30A


FEATURES:

- 1. AVAILABLE IN FINGER SAFE STYLE MODEL ONLY THAT INCLUDE END PLATES AND HINGED COVER
- 2. FINGER SAFE TO IP20. PER. IEC60529
- 3. cULus LISTED TO UL 1953 AND 1059
- 4. AL9CU RATED FOR USE WITH COPPER OR ALUMINUM CONDUCTOR CLASS B & C, AND OPERATING TEMP OF 90C
- 5. VOLTAGE RATING 600 V
- 6. DEFAULT SCCR (SHORT CIRCUIT CURRENT RATING) WITH CORRECT FUSING = 100KA
- 7. QUICK RELEASE LOCKING MECHANISM TO DISCONNECT FROM STD.35MM DIN RAIL
- 8. OVAL ALIGN MOUNTING HOLE AT BASE ON EITHER WIRE ENTRY END
- 9. MATERIAL: COVER AND END PLATES = LEXAN 500R POLYCARBONATE
- 10. MATERIAL: BASE AND SIDE PANELS = VALOX NYLON 6/6 GF30%
- 11. MATERIAL: CONNECTOR BLOCK 6061T6 ALUMINUM TIN PLATED
- 12. MATERIAL: WIRE PORT SCREWS, STEEL TIN PLATED
- 13. MATERIAL: CONNECTOR TO BLOCK SECURITY SCREW, STEEL TIN PLATED
- 14. MULTI-PORT GANGING OF SAME SIZE BLOCK (SML, MED, LRG)
- 15. MAXIMUM AMPACITY PER POLE = 350A
- 16. PRIMARY (LINE, RUN, MAIN) SIDE = 2/0 AWG
- 17. PRIMARY MAXIMUM TORQUE VALUE = 120 IN.LBF
- 18. PRIMARY STRIP LENGTH = .50"
- 19. MAXIMUM AMPACITY PER POLE = 350A
- 20. SECONDARY (LINE, RUN, MAIN) SIDE = 4-8AWG 35 IN.LBF, 10-14AWG 20 IN. LBF
- 22. SECONDARY STRIP LENGTH = .50"
- 23. BLOCK MUST BE MOUNTED SO THAT TAP SIDE IS INSTALLED ON SIDE WITH REMOVABLE TAB
- 24. ALL SCREWS ARE TO BE INTERNAL HEX DRIVEN


- NOTES:
- DIMENSIONS IN BRACKETS [] ARE IN MM ROUNDED OFF TO THE NEAREST MM, UNLESS OTHERWISE SPECIFIED AND ARE FOR REFERENCE ONLY
 - MATERIALS: BASE, POLE SEPERATING SIDE AND LOCK - NYLON 66 GF30%
BLOCK AND RETENTION SCREWS - TIN PLATED ALUMINUM
FINGER SAFE COVERS - POLYCARBONATE
BLOCK MOUNTING HARDWARE - STAINLESS STEEL
 - MAY BE USED IN ANY NUMBER OF POLES REQUIRED.



RUN SIDE



DIN RAIL STYLE



TAP SIDE

2: TORQUE VALUES

WIRE RANGE (MCM/AWG)	CONNECTOR SIZE									
	750	600	500	350	250	3/0	2/0	1/0	#2	#4
750 - 600	550	550								
500	550	450	450							
400	550	450	450							
350	550	400	400	400						
250	550	360	360	360	360					
4/0 - 3/0	550	250	250	250	250	250				
2/0	550	180	180	180	180	180	120			
1/0	550	180	180	180	180	180	80	80		
#1		150	150	150	150	150	65	65		
#2 - #3		150	150	150	150	150	65	65	65	
#4 - #6		150	110	110	110	110	55	55	35	35
#8				75			45	45	25	25
#10 - #14				35			25	25	15	15

NPDB -	26 -	2/0 -	1
NSI PRODUCT GROUP POWER DISTRIBUTION BLOCKS	1ST DIGIT = # OF PRIMARY COND. 2ND DIGIT = #OF SECONDARY COND.	MAXIMUM WIRE SIZE	NUMBER OF POLES

PROPRIETARY AND CONFIDENTIAL		NAME	DATE		
<small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NSI Industries. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NSI Industries IS PROHIBITED.</small> <small>DNA, UNLESS OTHERWISE NOTED, ARE IN INCHES. DECIMAL .001 ± .015 FRACTION 1/64 ± .005 ANGLES DO NOT SCALE DRAWINGS ± 1°</small>		DRAWN	XGP		6/3/2024
		CHECKED	SSM		6/3/2024
		ENG APPR.			
		MFG APPR.			
SEE NOTES		Q.A.		TITLE: POWER DISTRIBUTION BLOCKS	
SEE NOTES		COMMENTS: TO ORDER NSI PRODUCTS CALL UNITED STATES (704) 439-2420 FOR PRODUCT INFO: www.nsiindustries.com			
DIMENSIONS ARE IN INCHES		SIZE	DWG. NO.	MODEL NO.	REV
		C		NPDB-26-500-1	C
		SCALE:1:2 SOLIDWORKS 2022 SHEET 1 OF 1			