

FEATURES:

1. Material: TiN Plated CU
2. UL listed for U.S. & Canada.
3. Wire connector rated for 35Kv max.
4. Class B/C compressed, concentric, and compact copper conductor.
5. Expanded wire range when installed with dieless NSi compression tool (N12ID).
6. Dimensions are for reference only.



SC Series: SC-8



PROGRAM:	SOLIDWORKS
UPDATED:	9/2022
SALES REV:	A
SIZE:	B (11x17)



SCALE 6:1



COPPER COMPRESSION CONNECTOR TOOL AND DIE CHART (# OF CRIMPS PER SIDE)

WIRE SIZE	STRIP LENGTH	DIE COLOR	EXPANDED WIRE RANGE W/N12ID	COPPER COMPRESSION CONNECTOR TOOL AND DIE CHART (# OF CRIMPS PER SIDE)							
				NSI	GREENLEE & ILSCO	BURNDY	T&B	HUSKIE			
#8AWG	1/2"	RED	#8AWG	N1240 SERIES KC12-8 (1)	NSI-12 -	NSI-12 -	GREENLEE 1240 SERIES ILSCO ILC-12, ILC-15 KC12-8 (1) ILD-1 (2)	Y-35, Y750, PAT 750 U8CRT (1)	T&B TBM-15, TBM-14M 15520 (2)	HUSKIE EP510C -	-

