



WWC-G | Grey Winged Connectors

Temperature Rating: 105° C (221° F) Max.

Voltage Rating: 600V Max. Building wiring; 1000V Max. Fixtures and Signs

FOR UL LISTED AND CQC CERTIFIED

3 #10	3 #12 w/1 #16	4 #14 w/1 #16
4 #12	3 #14 w/1 or 2 #16	4 #14 w/1 #18
3 #12 w/1 #14	3 #14 w/1 or 2 #18	

FOR CSA AND CQC CERTIFIED

2 or 3 #10	3 #10 w/1 or 2 #14 or #16	4 #14 w/1 #16 or #18
3 or 4 #12	3 #12 w/1 or 2 #14, #16 or #18	1 #8 w/1 or 2 #10
1 #10 w/3 #18	3 #12 w/1 #14 or #16	1 #8 w/1 to 4 #16 or #18
1 #10 w/2 to 4 #12 or #14	3 #14 w/1 or 2 #16 or #18	



WWC-B | Blue Winged Connectors

Temperature Rating: 105° C (221° F) Max.

Voltage Rating: 600V Max. Building wiring; 1000V Max. Fixtures and Signs

FOR UL LISTED AND CQC CERTIFIED

1 or 2 #6	1 #8 w/3 #10	2 #10 w/3 #12
2 #8	1 #10 w/3 #12	3 #10 w/1 #12
2 to 4 #10	2 #10 w/1 #12	3 #10 w/2 #12
3 #12	2 #10 w/2 #12	

FOR CSA AND CQC CERTIFIED

2 or 3 #8	1 or 2 #8 w/1 to 4 #14	3 #10 w/1 #12
2 to 4 #10	3 #8 w/1 #12 or #14	3 #10 Sol w/2 #12 Sol
1 #8 w/1 to 3 #10	1 #10 w/2 or 3 #12	3 #10 Sol w/2 #12 Str
1 or 2 #8 w/1 to 3 #12	2 #10 w/1 to 3 #14	3 #10 Str w/2 #12 Str



WWC-GR | Green Grounding Connectors

Temperature Rating: 105°C (221° F) Max.

Use for Grounding Terminal Only

FOR UL LISTED, CSA AND CQC CERTIFIED

2 to 5 #12	1 #10 w/1 to 3 #14	3 #12 w/1 #14
2 to 4 #14	1 #12 w/1 to 3 #14	
1 #10 w/1 or 2 #12	2 #12 w/1 to 3 #14	



WWC-R | Red Winged Connectors

Temperature Rating: 105° C (221° F) Max.

Voltage Rating: 600V Max. Building wiring; 1000V Max. Fixtures and Signs

FOR UL AND CSA LISTED

- | | | |
|--|-------------------------------------|-------------------------------------|
| 1 #6 | 2 #10 w/2 #12 w/1 or 2 #16 or #18 | 2 #14 w/1 #16 w/1 to 3 #18 |
| 1 or 2 #8 | 2 #10 w/2 #12 w/1 #14 | 3 #14 w/1 to 3 #16, #18, #20 or #22 |
| 1 to 4 #10 | 2 #10 w/1 to 3 #12 or #14 | 3 #14 w/1 #16 w/1 or 2 #18 |
| 1 to 5 #12 | 2 #10 w/1 to 4 #16 or #18 | 4 #14 w/1 or 2 #16, #18, #20 or #22 |
| 1 to 6 #14 or #16 | 2 #10 w/2 #14 w/1 or 2 #16 | 4 #14 w/1 #16 w/1 #18 |
| 2 to 6 #18 | 2 #10 w/1 #16 w/1 to 3 #18 | 5 #14 w/1 #16 or #18 |
| 3 to 6 #20 | 3 #10 w/1 to 3 #16 or #18 | 1 #16 w/1 to 5 #18, #20 or #22 |
| 4 to 6 #22 | 3 #10 w/1 #12 | 1 #16 w/1 #18 w/1 to 3 #20 or #22 |
| 1 #6 w/1 #10 | 3 #10 w/1 or 2 #14 | 1 or 2 #16 w/1 #20 w/1 or 2 #22 |
| 1 #6 w/1 #10 w/1 #14 | 3 #10 w/1 #12 w/1 #16 or #18 | 1 #16 w/2 #20 w/1 or 2 #22 |
| 1 #6 w/1 or 2 #12 | 3 #10 w/1 #14 w/1 #16 | 2 #16 w/1 #18 w/1 to 3 #20 or #22 |
| 1 #6 w/1 #12 w/1 or 2 #14 | 3 #10 w/1 #14 w/1 or 2 #18 | 2 #16 w/1 to 4 #18, #20 or #22 |
| 1 #6 w/2 #12 w/1 #18 | 3 #10 w/1 #16 w/1 or 2 #18 | 2 #16 w/2 #20 w/1 or 2 #22 |
| 1 #6 w/2 #14 w/1 or 2 #16 | 1 #12 w/1 #14 w/1 to 3 #18 | 3 #16 w/1 to 3 #18, #20 or #22 |
| 1 #8 w/1 or 2 #10 | 1 #12 w/1 #16 w/1 to 3 #18 | 3 #16 w/1 #18 w/1 or 2 #20 or #22 |
| 1 #8 w/1 #10 w/1 or 2 #12 or #14 | 1 #12 w/1 to 5 #14, #16 or #18 | 3 #16 w/1 #20 w/1 or 2 #22 |
| 1 #8 w/2 #10 w/1 #14 | 1 or 2 #12 w/1 #14 w/1 to 3 #16 | 4 #16 w/1 or 2 #18, #20 or #22 |
| 1 #8 w/1 to 3 #12 | 1 or 2 #12 w/2 #14 w/1 or 2 #16 | 4 #16 w/1 #18 w/1 #20 or #22 |
| 1 #8 w/2 #12 w/1 or 2 #14 | 2 #12 w/1 to 4 #14, #16 or #18 | 4 #16 w/1 #20 w/1 #22 |
| 1 #8 w/1 to 4 #14 | 2 #12 w/1 #14 or #16 w/1 to 3 #18 | 5 #16 w/1 #18, #20 or #22 |
| 1 #8 w/1 to 5 #16 | 3 #12 w/1 to 3 #14, #16 or #18 | 1 #18 w/1 to 5 #20 or #22 |
| 1 #10 w/1 to 4 #12 | 3 #12 w/1 #14 w/1 or 2 #16 or #18 | 1 to 3 #18 w/1 #20 w/1 or 2 #22 |
| 1 #10 w/1 #12 w/1 to 4 #14, #16 or #18 | 3 #12 w/2 #14 w/1 #16 | 1 to 3 #18 w/2 #20 w/1 #22 |
| 1 #10 w/2 #12 w/1 or 2 #14 | 3 #12 w/1 #16 w/1 or 2 #18 | 2 #18 w/1 to 4 #20 or #22 |
| 1 #10 w/2 #12 w/1 to 3 #16 or #18 | 4 #12 w/1 #14 | 3 #18 w/1 to 3 #20 or #22 |
| 1 #10 w/3 #12 w/1 #14 | 4 #12 w/1 #14 w/1 #16 or #18 | 4 #18 w/1 or 2 #20 or #22 |
| 1 #10 w/1 to 5 #14, #16 or #18 | 4 #12 w/1 or 2 #16 | 5 #18 w/1 #20 or #22 |
| 1 #10 w/1 #14 w/1 to 4 #16 or #18 | 4 #12 w/1 #16 w/1 #18 | 1 #20 w/2 to 5 #22 |
| 1 #10 w/2 #14 w/1 to 3 #16 | 1 #14 w/1 to 5 #16 or #18 | 2 #20 w/1 to 4 #22 |
| 1 #10 w/1 #16 w/1 to 4 #18 | 1 #14 w/1 #16 w/1 to 3 #18 | 3 #20 w/1 to 3 #22 |
| 2 #10 w/1 #12 w/1 or 2 #14 | 1 #14 w/1 to 5 #20 or #22 | 4 #20 w/1 or 2 #22 |
| 2 #10 w/1 #12 w/1 to 3 #16 | 2 #14 w/1 to 4 #16, #18, #20 or #22 | 5 #20 w/1 #22 |



WWC-T | Tan Winged Connectors

Temperature Rating: 105° C (221° F) Max.

Voltage Rating: 600V Max. Building wiring; 1000V Max. Fixtures and Signs

FOR UL LISTED TO US AND CANADIAN SAFETY STANDARDS

- | | | |
|----------------------------|------------------------------|--------------------------------|
| 1 to 3 #10 | 1 #16 w/1 or 2 #14 w/1 #12 | 1 #18 w/1 to 4 #16, #14 or #12 |
| 1 to 4 #12 | 1 #16 w/1 or 2 #14 w/1 #10 | 1 #18 w/1 or 2 #10 |
| 1 to 5 #14 | 1 #16 w/1 to 4 #14 or #12 | 2 #18 w/1 to 4 #16 or #14 |
| 2 to 6 #20, #18 or #16 | 1 #16 w/1 or 2 #10 | 2 #18 w/1 or 2 #10 |
| 3 to 6 #22 | 1 #16 w/1 #12 w/1 #10 | 3 #18 w/1 to 3 #16, #14 or #12 |
| 1 #10 w/1 #8 | 2 #16 w/1 #14 w/1 or 2 #12 | 3 #18 w/1 or 2 #10 |
| 1 #12 w/1 or 2 #10 | 2 #16 w/2 #14 w/1 #12 | 4 #18 w/1 or 2 #16, #14 or #12 |
| 1 #12 w/1 #8 | 2 #16 w/1 #12 w/1 #10 | 4 #18 w/1 #10 |
| 2 #12 w/1 #10 | 3 #16 w/1 #14 w/1 #12 or #10 | 5 #18 w/1 #16 or #14 |
| 1 #14 w/1 or 2 #12 w/1 #10 | 4 #16 w/1 #12 w/1 #10 | 1 #20 w/1 to 4 #18, #16 or #14 |
| 1 #14 w/1 to 3 #12 | 2 #16 w/1 to 4 #14 | 2 #20 w/1 to 3 #18, #16 or #14 |
| 1 #14 w/1 or 2 #10 | 2 #16 w/1 to 3 #12 | 3 #20 w/1 or 2 #18, #16 or #14 |
| 2 #14 w/1 #12 w/1 #10 | 2 #16 w/1 or 2 #10 | 4 #20 w/1 or 2 #18, #16 or #14 |
| 2 #14 w/1 or 2 #12 | 3 #16 w/1 to 3 #14 | 1 #22 w/1 to 5 #20, #18 or #16 |
| 2 #14 w/1 or 2 #10 | 3 #16 w/1 or 2 #12 or #10 | 2 #22 w/1 to 4 #20, #18 or #16 |
| 2 #14 w/1 #8 | 4 #16 w/1 or 2 #14 or #12 | 3 #22 w/1 to 3 #20, #18 or #16 |
| 3 #14 w/1 #12 or #10 | 4 #16 w/1 #10 | 4 #22 w/1 or 2 #20, #18 or #16 |
| 3 #14 w/2 #12 | 5 #16 w/1 #14 | 1 #22 w/1 #20 w/1 or 2 #16 |
| 4 #14 w/1 #12 or #10 | 5 #16 w/1 #10 | 1 #22 w/1 #18 w/1 #16 |



WWC-N1 | Yellow Compact Winged Connectors

Temperature Rating: 105° C (221° F) Max.

Voltage Rating: 600V Max. Building wiring; 1000V Max. Fixtures and Signs

FOR UL LISTED TO U.S. & CANADIAN SAFETY STANDARDS AND CQC CERTIFIED

- | | |
|---------------------------|-------------------------------------|
| 1 #10, #12 or #14 | 1 #12 w/1 or 2 #14 or #16 |
| 2 or 3 #12 | 1 #12 w/1 or 2 #18, #20 or #22 |
| 2to 4 #14 | 2 #12 w/1 #14, #16, #18, #20 or #22 |
| 2 to 6 #16 or #18 | 1 #14 w/1 to 3 #16, #18, #20 or #22 |
| 3 to 6 #20 | 2 #14 w/1 or 2 #16, #18, #20 or #22 |
| 4 to 6 #22 | 3 #14 w/1 #16, #18, #20 or #22 |
| 1 #10 w/1 #12 | 1 #16 w/1 to 5 #18 or #20 |
| 1 #10 w/1 or 2 #14 or #16 | |
| 1 #10w/1 to 3 #18 | |



WWC-N2 | Red Compact Winged Connectors

Temperature Rating: 105° C (221° F) Max.

Voltage Rating: 600V Max. Building wiring; 1000V Max. Fixtures and Signs

FOR UL LISTED TO U.S. & CANADIAN SAFETY STANDARDS AND CQC CERTIFIED

- | | | |
|------------------------------|--------------------------------|---------------------------|
| 1 #6, #8, #10, #12 or #14 | 1 #8 w/1 #14 Str | 1 #14 w/1 to 6 #16 or #18 |
| 2 or 3 #10 | 1 #10 w/1 to 3 #12 | 2 #14 w/1 #16 or #18 |
| 2 to 5 #12 | 1 #10 w/1 to 4 #14, #16 or #18 | 1 #16 w/2 to 6 #18 |
| 2 to 6 #14, #16 or #18 | 2 #10 w/1 or 2 #12 or #14 | |
| 3 to 6 #20 | 2 #10 w/1 to 3 #16 or #18 | |
| 5 or 6 #22 | 1 #12 w/1 to 4 #14, #16 or #18 | |
| 1 #8 w/1 #10 Str | 1 #12 w/1 #14 w/1 to 4 #16 | |
| 1 #8 w/1 #10 Str w/1 #12 Str | 1 #12 w/2 to 5 #14, #16 or #18 | |
| 1 #8 w/1 to 3 #12 Str | 2 #12 w/1 #14, #16 or #18 | |